EXECUTIVE ORDER A-031-0056 New On-Road Heavy-Duty Engines

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

	Silai bo iii aii			STANDARDS	INTENDED	
MODEL	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE	& TEST PROCEDURE	SERVICE CLASS 2	ECS & SPECIAL FEATURES 3
YEAR	6HMXH07.7JTB	7.7	Diesel	Diesel	ННОО	OC, ECM, EGR, DDI, TC, CAC
2006 ENGINE (L			ENGINE N	IODELS / CODES (I		
7.7	<u>'</u>			J08E-TB / J08E-T	B (260)	
*				*		
•				*		
*				1 - CD- Jakana Cad	High Way 40 CFR 86 2	bc=Title 40, Code of Federal Regulations, Section 86.abc;

*=not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc; L=liter; hp=horsepower; kw=kilowatt; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=mutti fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

CNG/LNG=compressed/liquelied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=mutti fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;

LWM+ HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;
LWM+ HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;
LES=emission control system; TWC/OC=three-way/oxidizing catalyst; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; HO25/O2S=heated/oxygen sensor; GARB=gaseous carburetor; fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SFIMFI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR=exhaust gas recirculation; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; (2004may26) [ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.1 (urban bus) or 13 CCR 1956.8 (other than urban bus); 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, in g/bhp-hr, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.1 or 13 CCR 1956.8 are in parentheses.)

				T		CO		PM		нсно	
NMHC		NOx							EUPO	FTP	EURO
FTP FU	FURO	FTP	EURO	FTP	EURO	FTP	EURO	FIP			+
			 	2.5	2.5	15.5	15.5	0.10	0.10		<u> </u>
0.5	0.5		 		 			*	•	*	
•	* _				1			0.09	0.07	*	•
0.1	0.01	*	•	2.4	1.9						*
				3.125		19.375		0.125			
	0.5 0.1	NMHC FTP EURO 0.5 0.5	NMHC N FTP EURO FTP 0.5 0.5	FTP EURO FTP EURO 0.5 0.5 0.1 0.01	NMHC NOx NMH FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 * * * * * 0.1 0.01 * * 2.4	NMHC NOx NMHC+NOx FTP EURO FTP EURO 0.5 0.5 * 2.5 2.5 * * * * 2.4 1.9	NMHC NOx NMHC+NOx FTP FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 2.5 15.5 * * * * * * * 0.1 0.01 * * 2.4 1.9 1.1	NMHC NOx NMHC+NOX CO FTP EURO FTP EURO FTP EURO FTP EURO 0.5 0.5 * * 2.5 2.5 15.5 15.5 * * * * * * * * 0.1 0.01 * * 2.4 1.9 1.1 0.1 0.225 * * 3.125 19.375	NMHC NOx NMHC+NOX CO F FTP EURO FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 2.5 15.5 15.5 0.10 * <td< td=""><td>NMHC NO× NMHC+NOX CO PM FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO O.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.07 0.07 0.01</td></td<> <td>NMHC NOx NMHC+NOX CO PM HC FTP EURO FTP EURO FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 2.5 15.5 15.5 0.10 0.10 . * * * * * * * * * . * . * .</td>	NMHC NO× NMHC+NOX CO PM FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO FTP EURO O.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.10 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.01 0.07 0.07 0.01	NMHC NOx NMHC+NOX CO PM HC FTP EURO FTP EURO FTP EURO FTP EURO FTP 0.5 0.5 * * 2.5 2.5 15.5 15.5 0.10 0.10 . * * * * * * * * * . * . * .

g/bhp-tr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

day of December 2005. Executed at El Monte, California on this

Allen Jons, Chief

Mobile Source Operations Division